

OUR PICKLE INJECTOR IN OVERVIEW

Description /Model		P11	P17	P21	P21/57	P26	P26TS	P52TS
Number of needles		11	17	21	57	26	26	52
Number of needle rows		1	2	2	3	2	2	4
Lenght	ca. cm	150	150	150	150	175	173	173
Width	ca. cm	60	60	60	60	75	83	83
Height	ca. cm	185	185	185	185	205	210	210
Working width	ca. mm	280	265	280	280	345	345	345
Flow through height	ca. mm	210	210	210	210	210	220	220
Electric supply 400V / 50 Hz	kW	1,5	1,5	1,5	1,5	2,2	6	6
Pressure air connection	bar	--	--	--	6	-	6	6
Speeds		1	1	1	1	2	--	--
2 speeds		0	0	0	0	--	--	--
Infinitely variable speed		--	--	--	--	--	S	S
Stainless steel impeller pump		S	S	S	S	S	--	--
Stainless steel piston pump		0	0	0	0	0	0	0
Stainless steel rotary pump		--	--	--	--	--	S	S
Computer control system		--	--	--	--	--	S	S
Filter system		--	--	--	--	0	N	N

Description /Model		P54TS	P81TS	P102TS	P105TS	P184TS	P236TS
Number of needles		54	81	102	105	184	236
Number of needle rows		4	6	4	6	8	8
Lenght	ca. cm	175	225	225	175	225	250
Width	ca. cm	86	115	120	86	115	110
Height	ca. cm	220	250	220	220	250	220
Working width	ca. mm	365	480	605	365	480	605
Flow through height	ca. mm	190/220	190/220	190/220	190/220	190/220	190/220
Electric supply 400V / 50 Hz	kW	7	11	11	7	15	15
Pressure air connection	bar	6	6	6	6	6	6
Infinitely variable speed		S	S	S	S	S	S
Stainless steel impeller pump		--	--	--	--	--	--
Stainless steel piston pump		0	0	0	0	0	0
Stainless steel rotary pump		S	S	S	S	S	S
Computer control system		S	S	S	S	S	S
Filter system		N	N	N	N	N	N

S= Standard O= Option N= necessary

Changes reserved



Via Weingartner, 11 I - 39022 Lagundo-Merano
☎ +39 0473 497 700 📠 +39 0473 497 701
✉ info@eller.biz 🌐 www.eller.biz



Top quality through high tech



GB

PICKLE INJECTOR

PRESTOMAT



PICKLE INJECTOR

The high class pickle injector for a perfect injection of different products. Economical, powerful, ergonomical construction, individual field of range, beautiful shapped, user friendly and high quality manufactured. These are the efficient signs of the pickle injector PRESTOMAT.

This machine is needed for injecting ham, fish, poultry, cooked pickle products ect.

WATCH OUT YOUR ADVANTAGE

- Many-sided through a lot of additional equipment.
- Less service cost charges through perfect maintenace-friendly construction.
- Quick changeable needle systems without any tool.
- Extreme friendly cleaning through toolless removing of the conveyor belt.
- User friendly through well reasoned stainless steel impeller pump (standard) controll.
- Pre filter system (also with filter unit or storage container).
- Filter- and cleaning systems for optimal hygiene.
- It's possible to work products with or without bones



P52TS



Conveyor belt
according the food law out of plastic easy to clean through removing of the belt without any tools
Brine pre filter
out of stainless steel, easy to remove for cleaning



Down holder with brine recovery system



Different needle types



Quick-change needle system




Detail needle bar



P21



Adapter for poultry



Possible insert of steaker knife to enlarge the surface and for a better disintegration and connective of the product. Through the use of the steaker knife the tumbler time will be reduced and it will be an improvement to the consistence too.



P52TS

Microprocessor control



Comfortable Touch-screen control allows the most simple and easy to oversee operati the operator with dialogs through the menus. Stroke-height, needle-head speed, belt-feed, one or two way injection and the system pressure can be precisely adjusted.

Pumps



Impeller pump out of stainless steel



Lobe pump out of stainless steel for high injection and dense birne



Centrifugal pump standard for industrial machines

